

GENERAL STAINLESS STEEL STEM THERMOMETERS



SP-B-1

Dial: $\varnothing 1''$ (25mm)
Stem: $\varnothing 3.8 \times L127\text{mm}$
Range: $-10 \sim +100^{\circ}\text{C}$
 $0 \sim 200^{\circ}\text{F}$
Stainless steel case and stem, with plastic sleeve



SP-B-1C

Dial: $\varnothing 1''$ (25mm)
Stem: $\varnothing 3.8 \times L127\text{mm}$
Range: $0 \sim 300^{\circ}\text{C}$
Stainless steel case & ring and stem



SP-B-2

Dial: $\varnothing 1\text{-}3/4''$ (45mm)
Stem: $\varnothing 3.8 \times L127\text{mm}$
Range: $-10 \sim +100^{\circ}\text{C}$
 $0 \sim 200^{\circ}\text{F}$
Stainless steel case and stem, with plastic sleeve



SP-B-3

Dial: $\varnothing 1\text{-}3/8''$ (35mm)
Stem: $\varnothing 3.8 \times L127\text{mm}$
Range: $-40 \sim +70^{\circ}\text{C}$
 $-40 \sim +160^{\circ}\text{F}$
Stainless steel case and stem, with plastic sleeve



SP-B-3A

Dial: $\varnothing 1\text{-}3/8''$ (35mm)
Stem: $\varnothing 3.8 \times L127\text{mm}$
Range: $-10 \sim +100^{\circ}\text{C}$
 $0 \sim 200^{\circ}\text{F}$
Stainless steel case and stem, 1/4"NPT male thread connection



SP-B-4

Dial: $\varnothing 2''$ (50mm)
Stem: $\varnothing 6 \times L110\text{mm}$
Range: $54 \sim 88^{\circ}\text{C}$
 $130 \sim 190^{\circ}\text{F}$
Stainless steel case & crimp ring and stem



SP-B-4B

Dial: $\varnothing 2''$ (50mm)
Stem: $\varnothing 3.8 \times L150\text{mm}$
Range: $50 \sim 550^{\circ}\text{C}$
Stainless steel case & crimp ring and stem with clip and marker



SP-B-4D

Dial: $\varnothing 2''$ (50mm)
Stem: $\varnothing 3.8 \times L150\text{mm}$
Range: $0 \sim 200^{\circ}\text{C}$
 $50 \sim 400^{\circ}\text{F}$
Stainless steel case and stem

* Other stem lengths and scale ranges can be made by order.

GENERAL STAINLESS STEEL STEM THERMOMETERS



SP-B-4G

Dial: Ø2" (50mm)
Stem: Ø3.8 x L40mm
Range: 50 ~350°C
100~700°F
Stainless steel case &
crimp ring and stem
with nut

SP-B-4M

Dial: Ø2" (50mm)
Stem: Ø6 x L36mm
Range: 140~800°F
Stainless steel case &
ring and stem
with nut

SP-B-5

Dial: Ø2-1/2" (63mm)
Stem: Ø3.8 x L127mm
Range: 100~400°F
Stainless steel case &
crimp ring and stem

SP-B-5B

Dial: Ø2-4/5" (70mm)
Stem: Ø6 x L125mm
Range: 60~85°C
120~200°F
Stainless steel case &
crimp ring and stem



SP-B-6

Dial: Ø2-7/8" (70mm)
Stem: Ø6 x L120mm
Range: 50~100°C
100~290°F
Stainless steel case &
crimp ring and stem

SP-B-7

Dial: Ø2-3/8" (60mm)
Stem: Ø6 x L120mm
Range: 0~200°C
Aluminum case & crimp
ring, stainless steel stem

SP-B-8

Dial: Ø1-7/8" (48mm)
Stem: Ø3.8 x L127mm
Range: -10~+220°C
0~220°F
Stainless steel case &
crimp ring and stem

SP-B-9

Dial: Ø2" (50mm)
Stem: Ø6 x L130mm
Range: 54~88°C
130~190°F
Stainless steel case &
crimp ring and stem

* Other stem lengths and scale ranges can be made by order.