

GRILL & EQUIPMENT THERMOMETERS



SP-H-2

Dial: Ø2-1/2" (63mm)
Stem: Ø8 x L47 mm
Range: 0~120°C
40~240°F
Stainless steel case,
brass stem and thread



SP-H-2B

Dial: Ø2-1/2" (68mm)
Stem: Ø6 x L68mm
Range: 50~850°F
Stainless steel
1/4"NPT male thread



SP-H-7

Dial: 52 x 78 x 40mm
Range: 0~100°C
Plastic case, aluminum
stem with spring



SP-H-8

Dial: Ø3" (75mm)
Range: 0~100°C
Plastic case, aluminum
stem with spring



SP-H-10

Dial: Ø2-1/5" (56mm)
Stem: Ø6 x L37mm
Range: 10~350°C
50~700°F
Stainless steel
1/4"NPT male thread



SP-H-11

Dial: 75 x 47 mm
Stem: Ø8 x L47mm
Range: 0~300°C
100~600°F
Stainless steel



SP-H-12

Dial: Ø1-1/2" (40mm)
Stem: Ø9 x L58mm
Range: 0~60°C
Plastic case
brass stem and thread



SP-H-14

Dial: 36 x 47 mm
Stem: Ø6 x L20mm
Range: 10~350°C
50~700°F
Stainless steel



SP-H-15

Dial: Ø2" (50mm)
Stem: Ø6 x L20 mm
Range: 160~240°C
350~450°F
Stainless steel
With nut



SP-H-16

Dial: Ø2-3/5" (66mm)
Stem: Ø6 x L88mm
Range: 10~260°C
50~500°F
Iron case & stainless
steel stem, 1/4"NPT
brass male thread



SP-H-20

Dial: Ø3-1/2" or 5-1/2"
Stem: Ø6 x L20mm
Range: 50~300°C
100~600°F
Stainless steel
1/4"NPT male thread



SP-H-23

Dial: Ø2-2/3" (68mm)
Stem: Ø6 x L20mm
Range: 50~700°F
Stainless steel

* Other stem lengths, thread connections and scale ranges can be made by order.